

Crimp Contacts for Membrane Switches and Flexible Circuits

MHFFC106 Hi Flex Female

2.54mm Pitch



Stable Insertion Force for Flexible Mating Cycles

Suitable for use with MH Series Housings/Wafers

MLFC506 Low Force Female

2.54mm Pitch



Low Insertion Force for repeated Mating Cycles

Suitable for use with MH Series Housings/Wafers

MHFC025 High Force Female

2.54mm Pitch



High Retention for High Vibration Applications

Suitable for use with MH Series Housing/Wafers

MLFFSC506 Low Force Female Solder

2.54mm Pitch



Designed for Soldering directly to Flexible PCBs or Ultra Thin Rigid PCBs

MLST241 Long Male Solder Tab

2.54mm Pitch



Can be plugged into a socket

Ideal for Soldering directly into a PCB

MSST141 Short Male Solder Tab

2.54mm Pitch



Can be plugged into a socket

Ideal for Soldering directly into a PCB

Other styles of Contacts also available

For Samples, Data or Quotation, please contact us

MEMCON Limited

Compass House Vision Park Chivers Way HISTON
Cambridge CB24 9AD United Kingdom
T +44 1223 257724 F +44 1223 257800
www.memcon.eu sales@memcon.eu

MEMCON (Asia) Limited

Level 7 Parkview Centre
7 Lau Li Street Causeway Bay Hong Kong
T +852 3741 1411 F +852 3747 8980
www.memcon.asia sales@memcon.asia