

MCS-500AG SILVER CONDUCTIVE SCREEN PRINTABLE INK

MCS-500AG has been formulated as a Silver Conductive Screen Printable ink ideal for use in flexible circuit, membrane switch, touch switches and other flexible applications.

MCS-500AG is a general purpose polymer thick film silver-containing conductor for use only on print treated polyester or polycarbonate.

By using a unique combination of silver flake and the latest in resin technology, the MCS-500AG possesses excellent conductivity, abrasion resistance and printability.

It can be used with semi-automatic and manual printers and offers excellent residence time on the screen.

Appearance

Volume Resistivity (Ω /sq cm)

Adhesion/Tape Pull

Abrasion Resistance, Pencil Hardness

(ASTM D3363-74)

Solids Content

Viscosity (poise) (RION VT-04, #2 spindle 25°C)

Cure Conditions

Circuit Line Thickness

(printed with 270 mesh polyester)

Coverage

(dependent on screen size and material)

Shelf Life

Thick Silver Coloured Paste

≤0.5 x 10-4

100/100 (no material removal)

2H

65%

120 / 150

120°C for 10 mins

 5 ± 1 microns

20 x / 10 x / kg

6 mths in unopened container

Printing

Screen Type

Substrates

Cleanup Solvent

Storage

Suitable for Manual, Semi-Automatic or High Process's

Polyester or Stainless Steel

Polyester or Polycarbonate

MEK, MIBK, Acetone or similiar solvents

Store at ambient temp, some settling of solids may occur,

stir vigorously before use

Safety & Handling:

The following precautions should be exercised when handling:

Avoid prolonged contact with skin. If contact with skin occurs, wash immediately with soap and water

Use with adequate ventilation, avoid prolonged breathing of vapour.

Dangerous if swallowed - DO NOT CONSUME

The performance characteristics are influenced and affected by printing technique, nature of substrate, curing time, curing temperature and type of drying equipment.

Before adopting our products for commercial use, the user assumes responsibility for determining fitness of use in their particular application and process. Memcon makes no warranties and assumes no liability in connection with any use of this information.

MEMCON (Asia) Limited

Level 7 Parkview Centre 7 Lau Li Street Causeway Bay Hong Kong T +852 3741 1411 F +852 3747 8980 www.memcon.asia sales@memcon.asia

MEMCON Limited

Compass House Vision Park Chivers Way HISTON
Cambridge CB24 9AD United Kingdom
T +44 1223 257724 F +44 1223 257800
www.memcon.eu sales@memcon.eu

MEMCON® is a registered trade mark of Memcon Limited

Nemcon North America
3786 Stadium Drive Bridgman
Michigan 49106 USA
T+1 269 466 5632 F+1 269 466 6034
www.memcon.net sales@memcon.net