

## SINGLE SIDED SPACER TAPE

Our range of high performance spacer tapes have been specifically developed for use in membrane switch applications and associcated products. The spacer tapes which utilise high performance adhesive, provide a good level of initial tack and a high level of adhesive strength.

Developed for use in the harshest of conditions, our spacer tapes demonstrate outstanding resistance to hostile environments. They are ideally suited for die-cutting.

Our spacers are available in both double sided and single sided construction, in a wide variety of polyester carrier and adhesive thicknesses.

The MS series spacer tapes provide a high quality product at a price positioned to help our customers compete in this competitive market.



Part Number	MSS075-50A	MSS100-50A	MSS125-50A	MSS150-50A	MSS175-50A	MSS238-50A
Total Thickness, mm	0.075	0.100	0.125	0.150	0.175	0.238
Carrier Thickness, mm	0.025	0.050	0.075	0.100	0.125	0.188
Adhesive Thickness	0.05	0.05	0.05	0.05	0.05	0.05
Carrier Material/Colour	PET Clear					
Adhesion to Steel N/25mm	≥16	≥18	≥18	≥18	≥18	≥18
Adhesion to PET N/25mm	≥14	≥16	≥16	≥16	≥16	≥16
Holding Power, 25mm 1kg 25°C	> 4.5 Hrs	≥4.5 Hrs	≥ 4.5 Hrs	≥4.5 Hrs	>4.5 Hrs	≥4.5 Hrs
Working Temperature	-30~120°C	-30~120°C	-30~120°C	-30~120°C	-30~120°C	-30~120°C
Short Temperature	200°C	200°C	200°C	200°C	200°C	200°C
Sheet Size, mm	915 x 610 (S1)					
	1000 x 700 (S2)					
Roll Size	100M x 960mm					

The performance characteristics are those results obtained in our laboratory.

Before adopting our products for commercial use, the user assumes responsibility for determining fitness of use in their particular application and process.

## MEMCON Limited

Compass House Vision Park Chivers Way HISTON Cambridge CB24 9AD United Kingdom T+44 1223 257724 F+44 1223 257800 www.memcon.eu sales@memcon.eu Memcon makes no warranties and assumes no liability in connection with any use of this information.

## MEMCON (Asia) Limited

Level 7 Parkview Centre
7 Lau Li Street Causeway Bay Hong Kong
T +852 3741 1411 F +852 3747 8980
www.memcon.asia sales@memcon.asia